

From: Vanessa Steigerwald [mailto:vanessa.steigerwald@epa.state.oh.us]
Sent: Tuesday, March 03, 2009 3:00 PM
To: Nordine.John@epa.gov; Gunnarson, David
Cc: Steve Love; Steve Tuckerman
Subject: Comments on Haley's Ditch Risk Based Cleanup

John and Dave,

I have reviewed the "Application for Risk Based Cleanup of Soil at Haley's Ditch" dated January 9, 2009.

Please find below several comments that I have on this document:

1) Clean Fill PCB Concentrations: It is stated in the Executive Summary (page i) and in Section 2 that "The excavation areas, except the stream channel and wetlands, will be backfilled, as needed, with soil containing less than 1 mg/kg total PCBs. The restored stream channel and wetland areas will be covered with clean fill material containing less than 0.5 mg/kg PCBs." The soil cleanup action level is 1 mg/kg whereas the cleanup action level is less than 0.5 mg/kg PCBs for Haley's Ditch sediment. Setting the cleanup action levels and the clean fill material levels to the same values does not provide adequate "buffer" to account for sampling uncertainties and to ensure recontamination does not occur. Dave mentioned the possibility of reusing some of the fill material removed as part of the remediation activities instead of having to bring in all new fill. Ohio EPA cautions against reusing PCB contaminated fill material from the site due to sampling uncertainties and the potential for recontaminating remediated areas. It